


Basic Peristaltic Pump

WT600-2J

PERISTALTIC PUMP



Pump Head Options



YZ1515x
YZ2515x



YZII15
YZII25



KZ25



DG15-24

Speed	60rpm-600rpm, CW/CCW.
Speed resolution	1rpm
Speed accuracy	$\leq \pm 1\%$
Control mode	Control panel, external signal control and communication control are available.
Display	3-digit LED display for current speed
External control	Start/stop, direction and speed control (4-20mA, 0.5-5V, 1-10V, 1-10kHz external control module optional).
Communication interface	RS485
Power-off memory	Return to previous status when powered on
Prime	For fast filling and emptying at full speed
Dimension (L×W×H)	285×207×180 (mm)
Power supply	AC 220V±20%/200W or AC 110V±20%/200W
Operating temperature	0 to 40°C
Relative humidity	<80%
IP rating	IP31
Weight	5.2kg

Mainly used in laboratorial applications. With brushless motor, can drive multi-pump heads.



Model (Product code, Power supply)	Pump Head	Tubing	Flow Rate (mL/min)	Weight (kg)
WT600-2J-A (05.02.63A, AC220V)	(1, 2, 3, 4)×YZ1515x	13" 14" 19" 16" 25" 17" 18"	4-2200 (Single Channel)	5.6-6.8
	(1, 2, 3, 4)×YZII15			
WT600-2J-B (05.02.63B, AC110V)	(1, 2, 3, 4)×YZ2515x	15" 24"	100-1600 (Single Channel)	5.6-6.0
	(1, 2)×YZII25	15" 24" 35" 36"	100-3000 (Single Channel)	
	DG15-24	16" 25" 17"	50-1800 (Single Channel)	6.0
	(1, 2)×KZ25	15" 24" 35" 36"	200-6000 (Single Channel)	6.0-6.8